

RELYENCE DISTRIBUTOR PROGRAM



ESG-LED

COVE / CABINET / SHOWCASE / DISPLAY
RIGID LED SLEEK ELEMENT

Type

Project

Catalog No.



SPECIFICATIONS

Voltage	120V
Power Factor	> 90%**
CRI	80
Max Wattage for a Single Run	280W
Beam Angle	130°
Operating Temp *	4°F to 104°F
Lamp Life	50,000 hours
Dimensions	3/4" W x 1-3/8" H
Housing	Aluminum
Environment	Indoor - Dry / Damp
Certifications	
Warranty	5 Years – see published warranty terms for detailed information.

LUMEN DATA

Part Number	Watts	Color Temp	Lumens	Efficacy (lm/W)
ESG-LED-12	4	3000K	353	88
ESG-LED-12	4	4000K	380	95
ESG-LED-24	8	3000K	720	90
ESG-LED-24	8	4000K	780	97
ESG-LED-29	10	3000K	900	90
ESG-LED-36	12	3000K	1050	88
ESG-LED-36	12	4000K	1260	105
ESG-LED-48	15	3000K	1350	90
ESG-LED-48	15	4000K	1590	106
ESG-LED-60	18	3000K	1600	89
ESG-LED-60	18	4000K	1900	105

Suitable for mounting inside cabinet
Suitable for use in closet applications

*Exceeding the operating temperature values may damage the LEDs by reducing the lifespan, lumen output, adversely impact color consistency, and void the warranty. It is recommended adequate airflow and heatsinking be taken into consideration in the installation and application of this product. Improper thermal management may lead to premature product failure.

**12" & 24" fixtures have a power factor >80%

DESCRIPTION

JESCO's RELYENCE Series ESG-LED offers a low profile design with a minimal footprint for under-cabinet, over-cabinet, cove, showcase and display applications. Suitable for mounting inside cabinet and closet applications. Environmentally friendly with no Mercury and no UV or IR emission. Complete line of mounting and connecting accessories to meet any installation needs.

ORDERING INFORMATION

SERIES ESG-LED	-	LENGTH 12 - 12-3/8" 24 - 22-3/4" 29 - 28-1/2" 36 - 34-1/2" 48 - 46-1/4" 60 - 58"	/	COLOR TEMP 30 - 3000K 40 - 4000K	-	FINISH W W - White
--------------------------	---	---	---	---	---	---------------------------------

Example: ESG-LED-12-30-W



www.jescolighting.com
support@jescolighting.com
Tech Support: 855.592.0029

15 Harbor Park Drive
Port Washington, NY 11050
Main Line: 800.527.7796
Fax Line: 855.265.5768

219 South 6th Ave
City of Industry, CA 91746
Main Line: 855.654.0110
Fax Line: 626.333.2955

Specifications subject to change without notice.

RELYENCE DISTRIBUTOR PROGRAM



ESG-LED

COVE / CABINET / SHOWCASE / DISPLAY
RIGID LED SLEEK ELEMENT

Type

Project


Catalog No.

WIRING DIAGRAMS – For reference purposes only. Not for installation. Not drawn to scale.


INDIVIDUAL UNIT



CONNECTED WITH A DIRECT CONNECTOR



CONNECTED WITH A CONNECTING CABLE



HARDWIRE USING SG-B BOX



- A.** ESG-LED (Fixture)
- B.** SG-PCxx-W (Power Cord)
- C.** SG-DC (Direct Connector)
- D.** SG-CC-xx (Connecting Cable)
- E.** SG-Bx (Optional Hard Wire Box)

RELYENCE DISTRIBUTOR PROGRAM



ESG-LED

COVE / CABINET / SHOWCASE / DISPLAY
RIGID LED SLEEK ELEMENT

Type	
Project	
Catalog No.	

ACCESSORIES & COMPONENTS

	Part Number	Description		Part Number	Description
	SG-PC24-W SG-PC72-W SG-PC96-W SG-PC144-W	Power Cord & Plug 2' white 6' white 8' white 12' white		SG-CC6 SG-CC12 SG-CC24 SG-CC36 SG-CC48	Connecting Cable 6" white 12" white 24" white 36" white 48" white
	SG-PCL SG-PCLL	Right Angle Power Cord & Plug 6" (From back) 6" (From front)		SG-CC6L SG-CC12L SG-CC24L SG-CC36L SG-CC48L	Right Angle Connecting Cable 6" white 12" white 24" white 36" white 48" white
	SG-BM	Commercial Grade Metal Hard-Wire Box. Enables fixtures to be controlled by a wall switch. 2-3/4" L x 1-3/4" W x 1-3/4" H		SG-BM-SW	Commercial Grade Metal Hard-Wire Box with Switch. Enables fixtures to be controlled by a wall switch. 3-1/2" L x 2" W x 1-1/8" H
	SG-MC-A	Mounting Clip Adjustable. Stainless Steel.		SG-B	Plastic Hard-Wire Box with Switch. 3-5/8" L x 2-1/2" W x 1-3/8" H
	SG-MC-V	Mounting Clip 0° vertical mount. Stainless Steel. (2) Included with fixture.		SG-MC-VH	Mounting Clip 90° vertical mount. Vertical and horizontal mount. Stainless Steel.
	SG-MC-45	Mounting Clip 45° vertical mount. Stainless Steel.		SD-DC	Direct Connector

Note: All accessories also function with JESCO's SG-4 & SG-5 fluorescent and S201 & S401 LED fixtures for easy retrofitting or interconnecting.



www.jescolighting.com
support@jescolighting.com
Tech Support: 855.592.0029

15 Harbor Park Drive
Port Washington, NY 11050
Main Line: 800.527.7796
Fax Line: 855.265.5768

219 South 6th Ave
City of Industry, CA 91746
Main Line: 855.654.0110
Fax Line: 626.333.2955

Specifications subject to change without notice.